



PERFORMANCE EVALUATION OF PRE-CAST SLABS FOR CONTINGENCY RIGID AIRFIELD PAVEMENT DAMAGE REPAIR

October 27, 2010

REZA ASHTIANI, PHD

ATHAR SAEED, PHD, PE

Applied Research Associates, Inc.

MICHAEL HAMMONS, PHD, PE

Air Force Research Laboratory



Objectives



Mechanistic Characterization of pre-cast panels installed using different Leveling Materials and different Installation Techniques through:

- Analysis of Load Transfer Efficiency (LTE_{δ} , LTE_{σ} , and LT_{FAA})
- Analysis of Joint Stiffness
- Analysis of Deformation Energy Dissipated to the Pavement Foundation
- Analysis of Performance based on FE Response Analysis
 - Thermal Stresses
 - Load Induced Stresses (C-17 Aircraft)
 - Performance Index based on Failure Criteria



Construction and Installation Process






Test Sections



Variant	Pre-cast Panel ID.	Joint Orientation	Bonding Agent	Installation Method	HWD Direction
1	#1	East	HDP Foam	Direct Injection	East to West
2	#1	West	HDP Foam	Direct Injection	East to West
3	#2	East	HDP Foam	Deep Injection	East to West
4	#2	West	HDP Foam	Deep Injection	East to West
5	#3	East	Flowable Fill	Conventional	West to East
6	#3	West	Flowable Fill	Conventional	West to East
7	#3	East	Flowable Fill	Conventional	East to West
8	#3	West	Flowable Fill	Conventional	East to West





HWD Testing for Performance Analysis

*HWD Mid-Slab
Loading*

*HWD Edge Loading at
Different Load Repetitions*

*Back-Calculation of the
PCC Modulus*

*Determination of Load Transfer
Efficiency as a Function of
Number of Load Applications*

*Determination of Flexural
Strength (S_c)*

*Analysis of Joint
Stiffness*

*Analysis of Deformation
Energy*





Load Transfer in Rigid Pavements



Definition:


"Load Transfer" is a term used to describe the transfer (or distribution) of load across discontinuities such as joints or cracks (AASHTO, 1993).

$$LTE_{\delta} = \frac{d_u}{d_l} \times 100$$

$$LTE_{\sigma} = \frac{\sigma_u}{\sigma_l} \times 100$$

$$LT = \frac{LTE_{\sigma}}{1 + LTE_{\sigma}}$$

$$l = \sqrt[4]{\frac{Eh^3}{12k(1-\nu^2)}}$$



d_l, σ_l = Deflection and Vertical Stress under Loaded Slab

d_u, σ_u = Deflection and Vertical Stress under Unloaded Slab

l = Radius of Relative Stiffness

LTE_{σ} = Stress Based Load transfer Efficiency

LTE_{δ} = Deflection Based Load transfer Efficiency


LT = FAA criteria for Load Transfer Efficiency

$$LTE_{\delta} = \frac{\left[1206 \left(\frac{a}{l} \right) + 377 \right] LTE_{\sigma}^2 - 393 \left(\frac{a}{l} \right) LTE_{\sigma}^3}{1 + 689 \left(\frac{a}{l} \right) LTE_{\sigma} + \left[370 - 154 \left(\frac{a}{l} \right) \right] LTE_{\sigma}^2}$$



Load Transfer Efficiency Based on Deflections (LTE_{δ})

$$LTE_{\delta} = \frac{d_u}{d_l} \times 100$$




- ✕ Slab#1-East Joint-HDP Foam-EtW
- Slab#1-West Joint-HDP Foam-EtW
- + Slab#2-East Joint-HDP Deep Injection-EtW
- Slab#2-West Joint-HDP Deep Injection-EtW
- ◆ Slab#3-East Joint-Flowable Fill-WtE
- Slab#3-West Joint-Flowable Fill-WtE
- ▲ Slab #3-East Joint-Flowable Fill-EtW
- Slab#3-West Joint-Flowable Fill-EtW



Load Transfer Efficiency Based on Stresses (LTE_{σ})


$$LTE_{\delta} = \frac{\left[1206 \left(\frac{a}{l} \right) + 377 \right] LTE_{\sigma}^2 - 393 \left(\frac{a}{l} \right) LTE_{\sigma}^3}{1 + 689 \left(\frac{a}{l} \right) LTE_{\sigma} + \left[370 - 154 \left(\frac{a}{l} \right) \right] LTE_{\sigma}^2}$$





Load Transfer Based on FAA Design Criteria (LT)


$$LT = \frac{LTE_{\sigma}}{1 + LTE_{\sigma}}$$



- ✕ Slab#1-East Joint-HDP Foam-EtW
- Slab#1-West Joint-HDP Foam-EtW
- + Slab#2-East Joint-HDP Deep Injection-EtW
- Slab#2-West Joint-HDP Deep Injection-EtW
- ◆ Slab#3-East Joint-Flowable Fill-WtE
- Slab#3-West Joint-Flowable Fill-WtE
- ▲ Slab #3-East Joint-Flowable Fill-EtW
- Slab#3-West Joint-Flowable Fill-EtW




Initial and Terminal Joint Stiffness





Loss of Joint Stiffness after 1504 Load Repetition





Differential Energy Concept



- The dissipated energy to the subgrade is assumed to be proportional to the energy of elastic deformation
- Dissipated energy due to deformation of slab can be written as:

$$E = 0.5k\varepsilon_p^2$$


- k=Modulus of Subgrade Reaction
- ε_p =Plastic deformation at the edge of the slab
- The differential energy is defined as the energy difference in the elastic subgrade deformation under the loaded slab (leave) and unloaded slab (approach):

$$DE = E_L - E_{UL} = \frac{1}{2}k(\varepsilon_p)_L^2 - \frac{1}{2}k(\varepsilon_p)_{UL}^2$$

- Pavement systems with lower differential energy is expected to perform better in the field.



Differential Energy Concept



- Slab#1-East Joint-HDP Foam-EtW
- Slab#1-West Joint-HDP Foam-EtW
- Slab#2-East Joint-HDP Deep Injection-EtW
- Slab#2-West Joint-HDP Deep Injection-EtW
- Slab#3-East Joint-Flowable Fill-EtW
- Slab#3-West Joint-Flowable Fill-EtW
- Slab#3-East Joint-Flowable Fill-WtE
- Slab#3-West Joint-Flowable Fill-WtE



Effects of Environmental Conditions



Methodology



HWD Testing for Temperature Analysis

HWD Mid-Slab Loading at Different Times of the Day

HWD Edge Loading at Different Times of the Day

Back-Calculation of the PCC Modulus

Determination of Directional Load Transfer Efficiency

Determination of Flexural Strength (S_c)


Finite Element Modeling and Analysis of the Pre-Cast Slabs Subjected to C-17 Aircraft for Various Loading Positions

Determination of Critical Pavement Responses

Determination of Design Factor (Stress/Strength) for each Permutation




HWD TEST DROP SEQUENCE





Temperature Profile






Temperature Dependency of the Load Transfer Efficiency in Pre-Cast Panels



Day Time Superposition of Thermal and Load-induced Stresses for FWD Loading








Temperature Dependency of the Load Transfer Efficiency in Pre-Cast Panels



- Load Transfer Efficiencies were calculated as a function of time of the day and the temperatures were logged at each interval.
- Lowest recorded surface temperature was at 7:17 am as 85 °F and highest surface temperature was 107 °F at 13:57 pm.
- Load transfer efficiencies were relatively constant throughout the day.





Summary




Three pre-cast PCC slab installation techniques were investigated in this research effort




High Density Polyurethane (HDP) foam was used for leveling and installation of Slab#1 and Slab#2. Flowable fill was used for Slab#3

Performance of the repaired sections were assessed through analysis of:

- Load Transfer Efficiency Based on Deflections (LTE_{δ})
- Load Transfer Efficiency Based on Stresses (LTE_{σ})
- Load Transfer Based on FAA Design Criteria (LT)
- Analysis of Joint Stiffness based on MEPDG criteria [$\log (J_c)+R$]
- Analysis based on Dissipated Deformation Energy to Subgrade
- Analysis of Responses of Pre-Cast Panels using FE



Thank you!




HDP Foam Injection



Flowable Fill Installation Detail





Impact of Transverse Load Transfer Efficiency on Mid-Slab Deflections under HWD



$LTE_y=90\%$
 $LTE_x=100\%$



$LTE_y=90\%$
 $LTE_x=90\%$






Loading Configurations for FE Response Calculations




1




Corner Loading

2




Mid-Slab Loading

3



Edge Loading

4




Landing in the direction of dowel bars




*Direction of
Loading*

5



Landing perpendicular to the direction of dowel bars





Criteria for Different Runway Repair Strategies



- **EXPEDIENT REPAIR**

Expedient repairs are defined as airfield pavement repairs that create an initial operationally capable MOS/MOAS, based on projected mission aircraft requirements, in the most expeditious manner possible.

- **Criteria:** Criteria have been established for an expedient repair to provide an accessible and functional MOS/MAOS that will sustain **100 passes of C-17** with a gross weight of 227,707 kg (502 kips), or **100 passes of C-130** with a gross weight of 79,380 kg (175 kips).



- **SUSTAINMENT REPAIR**

Repair efforts designed to upgrade expedient repairs for increased aircraft traffic are known as sustainment repairs.

- **Criteria:** Sustainment repairs to an MOS/MAOS are expected to support **5,000 passes of C-17** with a gross weight of 227,707 kg (502 kips), or **5,000 passes of C-130** with a gross weight of 79,380 kg (175 kips).






Distribution of Vertical Stresses at the Top of the Subgrade (Day Time)






Distribution of Vertical Stresses at the Top of the Subgrade (Corner/Edge Loading for Slab#1)






Typical Day Time Curling






Top of the PCC Layer is *Warmer*
Bottom of the PCC Layer is *Cooler*

Typical Night Time Curling




Top of the PCC Layer is *Cooler*
Bottom of the PCC Layer is *Warmer*





Maximum Deflection under C-17 Landing Gear





Airfield Pavement Failure Models



- **Pavement Life is a function of the ratio between flexural strength and the bending stress used in the design (AC150/5320-6D)**

$$SCI = \frac{\left(\frac{S_c}{\sigma_v}\right) - 0.2967 - F_s(0.3881 + F_{SC}0.000039 \times SCI) \log COV}{0.002269}$$

$$COV = 5000 \times 10^{\frac{\left[\sqrt{\frac{S_c}{1.3\sigma_v}} - 1\right]}{0.07058}}$$

$$F_{SC} = \frac{0.392 - 0.3881 \times F_s}{0.0039 F_s}$$

- **COV= Coverage**
- **σ_v =Working stress in the design**
- **S_c =Flexural Strength $S_c = 6.5\sqrt{f'_c}$**
- **SCI=Structural Condition Index**



Design Factor [$\sigma_{v(max)}/S_c$]

